DAVISCOMMS

000S GTM

Features

- Functions as a standard GSM/GPRS modem.
- Panic button and over speed detection to alert remote host.
- Reset with KEY-ON function.
- Car alarm remote control.
- Memory capacity of up to 5000 standard reports.
- Cell ID report for location tracking when GPS signal is weak.
- Communication protocols: GSM (SMS), or GPRS (TCP/UDP) connection.

Configurable up to 10 SMS number lists, 10 GPRS profiles, 10 TCP/IP addresses, 10 UDP/IP addresses and programmable device ID.

- 20 geographical fences, 20 pre-programmable text messages and 20 event definitions.
- Firmware upgrade Over-The-Air (OTA) via TFTP (GPRS).
- Configuration and send data Over-The-Air (OTA) via SMS (GSM) and TCP/UDP (GPRS).
- Network ping operation and Keep-Alive heartbeat message.
- Voice call and silent call (local and remote auto-switchable).
- USB On-The-Go (OTG) ready.
- Supports loud speaker, internal and external MIC for voice call.
- Allows switch over between two SIM cards for border crossing.
- SMS center number and password protection.
- Mileage counters for distance notification.
- 12 programmable digital/analog input/output ports.
- External watchdog timer to prevent firmware lockup.
- Low power detection for battery and external power source.
- Programmable accelerometer setting for motion detection and power saving.
- Tamper sensing of antenna to alert remote host.
- Internal and external GSM, GPS antenna.
- GPS with Dead Reckoning.
- Configure the MTD2000 via MTD Configuration Software.


GSM/GPS/GPRS Mobile Tracking




Applications.

- · Vehicle tracking device.
- Anti-theft (with motion detection).
- Location Tracking via Personal Tracking System (PTS) integrated with Google Earth Software.
- Personal emergency alert with panic button.
- 2-way wireless communication.
- Tracking without GPS signals. (Tunnels, underground parking lots, etc, with Dead Reckoning tracking.)

System Setup __





^{*} Specifications subject to change without notice.

DAVISCOMMS (S) Pte Ltd

Blk 70 Ubi Crescent, #01-07 Ubi Techpark, Singapore 408570 Tel: (65) 65471127, Fax: (65) 65471129 **URL:** www.daviscomms.com.sg

DAVISCOMMS (UK) Limited

8. Manhattan House 401 Witan Gate, Milton Keynes Central Milton Keynes MK9 2BQ **England (United Kingdom)**

Tel: (44) 1908 609009, Fax: (44) 1908 609109 URL: www.daviscommsuk.com

Page 1 of 2

DAVISCOMMS

000S GTM

Specifications ___

Product Size : 128(L) x 71(W) x 38(H)mm : 120 grams (including battery) Weight

Environment Specification

- Standard operating temperature range:
 - -20 to 60°C (with internal battery)
- Extended operating temperature range:
 - -40 to +80°C (reduced specification, without internal battery)
- Storage temperature range:
 - -20 to +60°C

Electrical Specification

- RS232 communication port (RS232 or TTL)
- 12 Programmable Digital/Analog Input/Output ports:
 - 11 Programmable Input Ports (30V)
 - 4 Programmable sink/source output ports (30V / 1.2A)
 - 1 Programmable sink/source Fail-safe output port (30V / 1.2A)
 - 1 Programmable analog input (balance)
 - 1 Programmable analog output (30V / 10mA)
- Operating Voltage: 8 ~ 30V
- LED indicator: 1 X for GSM signal, 1 X for charging status, 1 X GPS fix

GSM/GPS/GPRS Mobile Tracking



GSM Module Specifications

(Siemens MC55i)


Quad Band : GSM (850/900/1800/1900)

GPRS : Multi-slot Class 10 SIM Card : Supports 1.8V and 3V SIM Card

GPS Module Specifications

(Ublox LEA-5M / 4R)

Frequency : L1 (1575.42MHz)



* Specifications subject to change without notice.

DAVISCOMMS (S) Pte Ltd

Blk 70 Ubi Crescent, #01-07 Ubi Techpark, Singapore 408570 Tel: (65) 65471127, Fax: (65) 65471129 **URL:** www.daviscomms.com.sg

DAVISCOMMS (UK) Limited

8. Manhattan House 401 Witan Gate, Milton Keynes Central Milton Keynes MK9 2BQ **England (United Kingdom)**

Tel: (44) 1908 609009, Fax: (44) 1908 609109 URL: www.daviscommsuk.com

Page 2 of 2